

EAMIPROOF S

Cold Applied Bitumen

Product Description

EAMIPROOF S is a low viscosity special blend of pure bituminous, designed to provide a high quality protective & waterproofing film.

Typical Applications

- As an external below ground coating for brickwork, concrete & steel structures.
- Damproof course membrane, horizontally & vertically.
- Internal waterproofing lining for water storage, concrete reservoirs & steel tanks.
- Rust protection of metal surfaces.
- External coating of pipes.
- As a curing compound for the freshly laid concrete.

Product Features

- Single component, easy to apply.
- Quick drying.
- Can be applied to damp concrete.
- Excellent adhesion to most substances.
- Cold applied bitumen coating.

Standards

EAMIPROOF S complies with BS 3416 Types 1 & 2, as a bituminous coating and with ASTM C-309 as a curing compound.

Guide for Application Surface Preparation

Surface to be coated should be sound, clean and free from any dust. Remove all loose particles, oil and greases. For steel preparation, surfaces should be blast cleaned to near white metal Swedish standard Sa 2 ½.

Coating

Apply by brush, roller or spray, a full coat of EAMIPROOF S and allow it to dry. Apply a second coat of EAMIPROOF S perpendicular to the first coat. If a thicker film is required, spray the whole area with coarse sand while the second coat is still tacky, then apply a third coat.

A geotextile mat could be applied between coats to reinforce the waterproofing layer.

Cleaning

Tools should be cleaned immediately with solvent after use.

Packaging

EAMIPROOF S is supplied in 20 lit. & 210 lit drums

Coverage

3.0 to 5.0 m² / lit. / coat depending on the nature of the substrate. It is recommended to cover the required area by two coats.

Technical Properties

Appearance	Black
Form	liquid
Specific Gravity	0.95
Drying Time	45 minutes
Time between Coating	24 hours

Storage

EAMIPROOF S should be stored in shaded areas.

Shelf Life

One year if stored properly in its original well closed container.

Health and Safety

- It is not allowed to smoke during application.
- Contact with skin should be avoided, any splashes should be washed with soap and water.
- Seek medical assistance in case of contact with eyes, after washing it with running water.

Warranty

We warrant our products to be of good quality & manufactured to rigid standards. This Warranty is in lieu of any & all other warranties expressed or implied.

This data sheet is published for information only. It is believed to be correct but no liability is accepted for it or the suitability of the product for any particular purpose. EAMIC TRETOL services are free & the company does not accept liability for any loss arising from it. Max liability is limited to substituting the same quality of material .

EAMIC TRETOL

Leaders in Construction Chemical Technology

Tretol is a member of the  International Group of Companies

Edition 01.2019

Cairo : 2Hadaek El Obour , Salah Salem St. Nasr City – Cairo Egypt Tel : (202) 22636220/24011024/22619414 Fax : (202) 22639002
Alex : 37 Ismail Serri Street Smouha- Alexandria Tel : (203) 4255066 Fax : (203) 4255066

www.eamicegypt.com

